



# WESLEY

## International

ENGINEERED-TO-ORDER MATERIAL HANDLING SOLUTIONS

### Model SCT 7750

Shown with  
optional hitch



#### Standard Features

- Dual Front Wheels
- Programmable Characteristics
- Sealed 350 Amp Controller
- Tamper-proof Speed Control
- Regenerative Braking
- Electronic Throttle Control
- On-board Diagnostics
- Maintenance Management System
- Contactor-less Drive System
- Sealed Direct Drive Transaxle
- Sealed On-board Automatic Charger
- Battery Discharge Indicator
- LCD Hour Meter
- Genuine 14 Gauge Diamond Plate Steel Chassis
- Parking Brake

**We build custom vehicles, too!**

#### WESLEY INTERNATIONAL

3680 Chestnut Street  
Scottsdale, GA 30079  
Toll Free (866) 370.7258  
Phone (404) 292-7441  
Fax (404) 292-8469  
[www.wesleypackmule.com](http://www.wesleypackmule.com)

## PACK MULE STOCK CHASER SCT SERIES

Industrial environments demand a special kind of equipment. That's why Wesley International's electric vehicles are meticulously engineered for safety, reliability and low maintenance. From the dual front wheels to the sealed motor, Wesley's vehicles offer increased stability and reduced down time. As a result, our Power Mule™ has been the choice of discerning buyers for years. They know that increased productivity and reduced maintenance costs deliver greater profit.

The Power Mule SCT 7750 stock chaser carries materials and tows up to 5,000 lbs. It is perfect for manufacturing facilities, airports, warehouses, parts distribution centers, greenhouses and more. If our standard size doesn't fit your needs, we will custom build a vehicle that is just right for you. Our custom equipment is made with the same commitment to quality, safety and reliability.

Why buy a Power Mule? Unique safety features, increased productivity, reduced maintenance and custom design... Can you afford not to buy a Power Mule?

Shown with  
optional hitch



MODEL SCT 7750

## POWER MULE STOCK CHASER SCT SERIES

SPECIFICATIONS	SCT 7750
Maximum Personnel	1
<b>DIMENSIONS</b>	
Length	78 in. (198.1 cm)
Width	32 in. (81.8 cm)
Height	50 in. (127 cm)
Wheel Base	40 in. (101.6 cm)
Ground Clearance	3 in. (7.6 cm)
Deck Height	24 in. (61 cm)
Deck Size	31.5 in. (80.0 cm) x 48 in. (121.9 cm)
Turning Radius	79 in. (200.7 cm)
<b>CAPACITIES*</b>	
Load Capacity	1200 lb. (544.3 kg)
Towing Capacity	5000 lb. (2268 kg)
<b>WHEELS &amp; TIRES</b>	
Wheels	4
Tires Pneumatic	4.80 x 8 LR B
<b>ELECTRICAL</b>	
Battery Type	220 amp hour
System Voltage (Battery Quantity)	36 volt (6-6 volt) / 48 volt (6-8 volt)
Sealed Motor (separately excited)	7.5 hp / 10 hp
Sealed Programmable Controller	350 amp
Automatic Built-in Charger	25 amp, 115 volt, 60 hz
Instrumentation	LED Battery Discharge LCD Hour Meter
Removable Key Switch	3-Position Safety Key
Horn	Push Button on Console
<b>TRANSAXLE &amp; TRANSMISSION</b>	
Sealed Drive Axle	Heavy-duty Direct Drive Helical Gear
Transmission Ratio	17.00:1
Programmable Maximum Speed	11 mph / 14 mph
<b>STEERING, BRAKES &amp; SUSPENSION</b>	
Steering	3-Spoke Contour Wheel
Service Brakes	Self-adjusting Wheel Drum Brakes
Electronic Brakes	Programmable Electronic Regenerative Braking
Park Brake	Pedal-Style Parking Brake

\* Not to be combined. Can carry load or tow.

### Optional Equipment

- Perma-Key Switch
- Removable Battery System
- Battery Cart with Charger
- 245 Amp Hour Batteries
- Ergonomic Anti-Fatigue Mat
- Diagnostic Handset
- Extended Deck Lengths
- Headlight
- Taillight
- Back-up Alarm
- Proximity Alarm
- Flashing Safety Beacon
- Rubber Deck Cover
- Small / Large Clipboard
- Non-marking Tires
- Dura Solid Tires
- Various Hitches
- 5 or 6-Step Ladder (87" or 95")

Specifications subject to change without notice.

Wesley International electric vehicles are designed to conform with ANSI B56.8 and OSHA standards.

**DISTRIBUTED BY:**