

# PERSONNEL CARRIER PC-300<sup>NXG</sup>

TOW LOAD- 2,000 LBS



PACK MULE



AC  
STANDARD

OUTPERFORMS  
OUTSMARTS  
OUTRUNS  
IT'S NXG



VEHICLE MIGHT BE SHOWN WITH OPTIONAL EQUIPMENT

## STANDARD FEATURES ON OUR PC-300<sup>NXG</sup>

AC DRIVE SYSTEM • INDUSTRY LEADING 3 YEAR WARRANTY • DUAL FRONT WHEELS • TWO PASSENGERS • PROGRAMMABLE PERFORMANCE CHARACTERISTICS (MAXIMUM SPEED, ACCELERATION RATE, ETC.) • HEAVY DUTY 245 AMP/HOUR BATTERIES • PREMIUM ON-BOARD HIGH FREQUENCY CHARGER WITH TEMPERATURE COMPENSATION & AUTOMATIC CELL EQUALIZATION TO EXTEND THE LIFE OF THE BATTERIES • SEALED DIRECT DRIVE TRANSAXLE • HEAVY DUTY HORN • UNIVERSAL HITCH PLATE • DASHBOARD SMART GAUGE (L. E.D. BATTERY STATUS, HOUR METER & DIAGNOSTIC CODES) • STATE-OF-THE ART, FULLY SEALED, TAMPER PROOF & PROGRAMMABLE CONTROLLER WITH ON-BOARD DIAGNOSTICS • PROGRAMMABLE REGENERATIVE BRAKING • EXTRA HEAVY-DUTY STEEL CONSTRUCTION (10 GAUGE UNI-BODY INTERNAL FRAME & 14 GAUGE GENUINE DIAMOND PLATE EXTERIOR) • HALL EFFECT ELECTRONIC THROTTLE • CONTACTOR-LESS DRIVE SYSTEM • 6 PLY LOAD RANGE C TIRES • TILLER STEERING COIL SPRING SUSPENSION

# PERSONNEL CARRIER PC-300<sup>NXG</sup>



STOCK CHASERS • BURDEN CARRIERS • TOW TRACTORS • MAINTENANCE VEHICLES • PERSONNEL CARRIERS

## OPTIONAL EQUIPMENT

- UPGRADE TO MAINTENANCE FREE AGM 260 AMP/HOUR BATTERIES
- ROLL OUT BATTERY EXCHANGE SYSTEM
- CARTS WITH CHARGERS FOR ROLL OUT BATTERIES
- SOLID NON-MARKING SOFT TIRES
- SOLID SOFT RUBBER TIRES
- BACK-UP ALARM
- PROXIMITY ALARM
- FLASHING SAFETY BEACON
- HEAD LIGHT, TAIL LIGHT, BRAKE LIGHT
- HAND LEVER PARKING BRAKE
- AUTOMOTIVE STEERING SYSTEM
- HANDLE BAR STEERING
- GALVANIZED & STAINLESS STEEL DECKS
- GALVANIZED FRAME
- PROTECTIVE FRONT GUARD WITH RUBBER BUMPERS
- STAKE BED
- CUSTOM CARGO RESTRAINTS
- MOUNTED CLIPBOARDS (LARGE AND SMALL)
- VARIETY OF HITCHES
- PERMA-KEY SWITCH
- PROGRAMMABLE KEY SWITCH
- 12 VOLT POWER SUPPLY FOR ELECTRONIC DEVICES
- DIAGNOSTIC HANDSET
- 6,000 TOWING CAPACITY
- CUSTOM COLORS
- HIGH CAPACITY ON-BOARD CHARGER, REDUCES CHARGE TIME BY UP TO 30% (48 VOLT ONLY)
- MAINTENANCE MANAGEMENT SYSTEM
- AUTOMATIC ELECTRIC PARKING BRAKE
- BLUE SAFETY LIGHT

## DIMENSIONS

- LENGTH- 86.5" (219.7 CM)
- WIDTH – 32" (81.3 CM)
- HEIGHT – 39" (99.1 CM)
- WHEEL BASE- 53.5" (135.9 CM)
- GROUND CLEARANCE – 3" (7.6 CM)
- DECK HEIGHT – 24" (61 CM)
- DECK – REAR: 31.5" (80 CM) X 19.5" (49.6 CM)
- TURNING RADIUS – 63.5" (161.3 CM)

## CAPACITIES

- MAXIMUM PERSONNEL – 2
- DECK – 750LBS. (340.2 KG)
- TOWING – 2,000 LBS. (907.2 KG)

## WHEELS & TIRES

- WHEELS – 4
- TIRES – PNEUMATIC 4.80 X 8 LRC (6 PLY)

## ELECTRICAL

- BATTERIES – 245 AMP-HR LEAD ACID, COMMERCIAL
- SYSTEM VOLTAGE (BATTERY QUANTITY) – 24 V (4 - 6V), 36 V (6 - 6 V), 48 V (6 - 8 V)
- SEALED AC MOTOR – 9.7 HP (24V), 13.2 (36V), 17.7 HP (48V)
- SEALED PROGRAMMABLE CONTROLLER – 300 AMP (24V), 330 AMP (30V & 48V)
- ON-BOARD HIGH FREQUENCY CHARGER – 25 AMP (24 V), 21 AMP (36V), 18 AMP (48 V)
- KEY SWITCH- REMOVABLE SAFETY KEY SWITCH
- HORN – HD

## STEERING, BRAKES & TRANSAXLE

- STEERING – TILLER
- SERVICE BRAKES – MECHANICAL SELF-ADJUSTING DRUM BRAKES
- ELECTRONIC BRAKES – PROGRAMMABLE ELECTRONIC REGENERATIVE BRAKING
- PARKING BRAKE – FOOT- OPERATED PARKING BRAKE
- HEAVY DUTY SEALED TRANSAXLE – HEAVY-DUTY DIRECT DRIVE HELICAL GEAR WITH 12.44:1 RATIO
- SUSPENSION – COIL SPRING REAR

AMERICAN  
BUILT



Call 800-241-2869

[www.packmule.com](http://www.packmule.com)  
[www.wesleyinternational.com](http://www.wesleyinternational.com)