

# TUGGER PMT-4500<sup>NXG</sup>

## HEAVY TOW - 5,000LBS



PACK MULE



OUTPERFORMS  
OUTSMARTS  
OUTRUNS  
IT'S NXG



### STANDARD FEATURES ON OUR PMT-4500<sup>NXG</sup>

VEHICLE IS SHOWN WITH OPTIONAL EQUIPMENT

**AC DRIVE SYSTEM • INDUSTRY LEADING 3 YEAR WARRANTY • DUAL FRONT WHEELS • PROGRAMMABLE PERFORMANCE CHARACTERISTICS (MAXIMUM SPEED, ACCELERATION RATE, ETC.) • HEAVY DUTY 245 AMP/HOUR BATTERIES • PREMIUM ON-BOARD HIGH FREQUENCY CHARGER WITH TEMPERATURE COMPENSATION & AUTOMATIC CELL EQUALIZATION TO EXTEND THE LIFE OF THE BATTERIES • PRECISION TRACK, RACK & PINION STEERING • SEALED DIRECT DRIVE TRANSAXLE • HEAVY DUTY HORN • HALL EFFECT ELECTRONIC THROTTLE • DASHBOARD SMART GAUGE (L.E.D. BATTERY STATUS, HOUR METER & DIAGNOSTIC CODES) STATE-OF-THE-ART, FULLY SEALED, TAMPER PROOF & PROGRAMMABLE CONTROLLER WITH ON-BOARD DIAGNOSTICS • PROGRAMMABLE REGENERATIVE BRAKING • EXTRA HEAVY-DUTY STEEL CONSTRUCTION (10 GAUGE AND 7 GAUGE UNI-BODY INTERNAL FRAME & 14 GAUGE GENUINE DIAMOND PLATE EXTERIOR) • CONTACTOR-LESS DRIVE SYSTEM UNIVERSAL HITCH PLATE • CONTOUR STEERING WHEEL • COIL SPRING SUSPENSION**

# TUGGER PMT-4500<sup>NXG</sup>



**STOCK CHASERS • BURDEN CARRIERS • TOW TRACTORS • MAINTENANCE VEHICLES • PERSONNEL CARRIERS**

## OPTIONAL EQUIPMENT

- UPGRADE TO MAINTENANCE FREE AGM 260 AMP/HOUR BATTERIES
- ROLL OUT BATTERY EXCHANGE SYSTEM
- CARTS WITH CHARGERS FOR ROLL OUT BATTERIES
- SOLID SOFT TIRES
- SOLID NON-MARKING SOFT TIRES
- BACK-UP ALARM
- PROXIMITY ALARM
- FLASHING SAFETY BEACON
- HEAD LIGHT, TAIL LIGHT, REVERSE & BRAKE LIGHT
- HAND LEVER PARKING BRAKE
- GALVANIZED & STAINLESS STEEL DECKS
- GALVANIZED FRAME
- PROTECTIVE FRONT GUARD WITH RUBBER BUMPERS
- DECK SHELVES
- STAKE BED
- CUSTOM CARGO RESTRAINTS
- MODULAR WORK STATION
- MOUNTED CLIPBOARDS (LARGE AND SMALL)
- VARIETY OF HITCHES
- PERMA-KEY SWITCH
- PROGRAMMABLE KEY SWITCH
- 12 VOLT POWER SUPPLY FOR ELECTRONIC DEVICES
- DIAGNOSTIC HANDSET
- 6,000 TOWING CAPACITY
- EXTERNAL CHARGER
- BLUE SAFETY LIGHT
- HIGH CAPACITY ON-BOARD CHARGER, REDUCES CHARGE TIME UP TO 30% (48 V ONLY)
- AUTOMATIC ELECTRIC PARKING BRAKE
- BUCKET SEAT
- 360 V, 330 AMP/HR INDUSTRIAL BATTERY
- MAINTENANCE MANAGEMENT SYSTEM

## DIMENSIONS

- LENGTH: 85.5" (217.2 CM)
- WIDTH: 38" (96.5 CM)
- HEIGHT: 45" (114.3 CM)
- WHEEL BASE: 61" (154.9 CM)
- GROUND CLEARANCE: 3" (7.6 CM)
- DECK HEIGHT: 24" (61 CM)
- DECK: FRONT: 37.5" (95.3 CM) X 18" (45.7 CM)  
REAR: 37.5" (95.3 CM) X 25" (63.5 CM)
- TURNING RADIUS: 79" (200.7 CM)

## CAPACITIES

- MAXIMUM PERSONNEL: 2
- DECK: 1,000LBS. (453.6 KG)
- TOWING: 5,000 LBS. (2,268 KG)

## WHEELS & TIRES

- WHEELS: 4
- TURF TIRES: FRONT: 165/65 X 8 LR C  
REAR: 205/50 X 10 LR B

## ELECTRICAL

- BATTERIES: 245 AMP-HR LEAD ACID, COMMERCIAL
- SYSTEM VOLTAGE (BATTERY QUANTITY): 36 V (6 - 6 V), 48 V (8 - 6 V)
- SEALED AC MOTOR: 13.2 HP (36 V), 17.7 HP (48 V)
- SEALED PROGRAMMABLE CONTROLLER: 330 AMP (36 V & 48 V)
- ON-BOARD HIGH FREQUENCY CHARGER: 21 AMP (36 V), 18 AMP (48 V)
- KEY SWITCH: REMOVABLE SAFETY KEY SWITCH
- HORN: PUSH BUTTON ON CONSOLE
- LEFT FOOT OPERATOR'S PRESENCE SWITCH

## STEERING, BRAKES & TRANSAXLE

- STEERING: 3 SPOKE CONTOUR WHEEL
- SERVICE BRAKES: SELF-ADJUSTING WHEEL DRUM BRAKES
- ELECTRONIC BRAKES: PROGRAMMABLE ELECTRONIC REGENERATIVE BRAKING
- PARKING BRAKE: FOOT-OPERATED PEDAL
- HEAVY DUTY SEALED TRANSAXLE: HEAVY-DUTY DIRECT DRIVE HELICAL GEAR WITH 16.99:1 RATIO
- SUSPENSION: COIL SPRING REAR

AMERICAN  
BUILT



SPECIFICATIONS ARE SUBJECT  
TO CHANGE WITHOUT NOTICE



**Call 800-241-2869**

[www.packmule.com](http://www.packmule.com)  
[www.wesleyinternational.com](http://www.wesleyinternational.com)